



Lis	Referencia	Salida de humos Ø	Dimensiones (AxHxL)
Lis	LIS8-7777	80 mm	430 x 910 x 530 mm
Mando a distancia BASIC	VATL	-	-

ESP

35

Estufa de pellet de aire Lis destaca por su alta temperatura de salida frontal a 100°C, gracias a su potente intercambiador HOTAIR®. Los contornos redondeados en la parte superior e inferior confieren un toque de modernidad a la vez que de elegancia. Según el tamaño de su vivienda podrá optar por una gama de estufas con este innovador diseño. Un altísimo rendimiento de 94,8% será la mejor garantía para el ahorro diario en combustible.

ENG

Lis air pellet stove stands out for its high front outlet temperature of 100 ° C, thanks to its powerful HOTAIR © exchanger. The rounded contours at the top and bottom give a touch of modernity as well as elegance. Depending on the size of your home, you can choose a range of stoves with this innovative design. A very high performance of 94.8% will be the best guarantee for daily fuel savings.



 Potencia nominal
Nominal heat output

7,5 kw

 Potencia máxima
Maximum power

10 kw

 Consumo
Consumption

0,6 - 1,7 Kg/h

 Temp
Salida
Output

100°C

 m³/
hora

235m³/h

 η

94,8%

 dB

39dB

 kg

68kg

 m²

75m²

 kg

14kg

 Colores
Colour



 Certificación
Certifications



 Medidas
Measures



ESP

- Incluye vermiculita en cámara de combustión
- Brasero de acero inoxidable
- Programación diaria, semanal y fin de semana
- Salida de humos posterior (T 90)
- Modulación automática y protección contra sobrecaleamiento
- Sensor de temperatura
- Control de temperatura en salida de humos
- Display vertical ocultable

OPCIONAL

- Control remoto vía internet (Kit WIFI)
- Mando a distancia

ENG

- Vermiculite in combustion chamber
- Stainless steel firepot
- Daily, weekly and weekend programming
- Smoke outlet: rear (T90)
- Automatic modulation and overheating protection
- Temperature sensor
- Smoke temperature control
- Concealed vertical display

OPTIONAL

- Internet remote control (Kit WIFI)
- Remote control